Mexapol®

High solids floor polish





High solids metallised emulsion floor polish which dries to a durable, high gloss finish.

Excellent levelling properties for easy application & to ensure a smooth even finish.



Very scuff & slip resistant making the floor easier to clean & maintain.



- · Responds to high & ultra high speed burnishing.
- Suitable for a variety of floors including vinyl, rubber, linoleum, terrazzo, marble & sealed surfaces.
- Ideal in heavy traffic areas.
- Coverage per 5 litre 400/500 sq. metres for 1 coat.
- · Approved for POLYFLOR flooring.

POLISH:

Ensure floor is dry, clean & neutral.

Use undiluted.

Pour polish into clean bucket or tray, alternatively pour directly onto floor in a thin line. Place clean mop or applicator into polish & spread thinly & evenly in WEST to EAST direction. Leave to dry for approximately 30 minutes.

Apply a further coat thinly & evenly at right angles to first coat (i.e. NORTH to SOUTH). Leave a 10 cm gap at the floor edge to avoid a build up.

Leave to dry for approximately 30 minutes.

A third coat may be required in heavy traffic areas or on old or worn floors.

RELATED ITEMS:

- Enhance[™] Ultra high solids floor polish.
- Sus-tain® Medium solids floor polish.
- · Clean & Shine Neutral floor maintainer.
- Floor & Carpet Care Guide.





Order Code: A074EEV2

Pack: 2 x 5 litre (10.87 kg) Pallet: 60 Packs

PRODUCT INFORMATION:

Appearance: Opaque white liquid Odour: Characteristic pH - undiluted: 8.5

Shelf life: 3 years

COMPOSITION:

Contains an aqueous dispersion of metallised acrylic co-polymers, wax emulsion, plasticisers, coalescent, defoamer, levelling agent & preservative.

BIODEGRADABILITY:

All surfactants used in Evans Vanodine products comply with the current European Regulations concerning biodegradability & protection of the environment.

QUALITY ASSURANCE:

This product is manufactured in the U.K. by EVANS VANODINE INTERNATIONAL PLC under an ISO 9001 Quality Management System Cert. No. FM 09535 and an ISO 14001 Environmental Management System Cert. No. EMS 506072 registered by the British Standards Institution.

REVISION DATE:

01/06/16





